




**INSTRUCTIONS FOR:
RATCHET LOAD BINDER 7.9-9.5MM 2500KG/
9.5-12.7MM 4200KG CAPACITY
MODEL No's: LB001, LB002**

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.

 **IMPORTANT: READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THE TOOL CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.**

1. SAFETY INSTRUCTIONS

- WARNING!** Failure to use this load binder properly may result in serious injury or even death to you or others.
- DO NOT** operate the load binder while standing on the load, stand on the ground. Be aware that ice, snow, rain, oil can affect your footing. Wear suitable non slip footwear.
- Move the handle with caution, it may whip, keep your body clear and out of the path of the moving handle.
- Make an inspection prior to each use, make sure that the spindles move easily within the travel range and that no damage is noticeable. In the event of damage such as: deformation, cracks, signs of severe wear or signs of corrosion the binder must not be used any more.
- Familiarise yourself with the regulations regarding size and number of chain systems required for securing loads on trucks etc.
- Chain tension may decrease due to load movement during transport. Check tension after periodically.
- Consider the safety of nearby workers as well as your own safety when using the load binder.
- The load binder must not bear against an object whilst under tension as this will cause a side load.
- Use the load binder in a well lit location.
- DO NOT** use this product to perform a task for which it is not designed.
- DO NOT** use whilst under the influence of drugs, alcohol or intoxicating medication.

- WARNING!** Failure to heed safety and warning instructions may result in damage and/or personal injury and will invalidate the warranty.
- WARNING!** *The warnings, cautions and instructions referred to in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.*

2. INTRODUCTION & SPECIFICATION

Manufactured from heat treated, drop forged steel for added strength. Suitable for clamping, binding, anchoring and tying down large loads. Ideal for farmers and HGV drivers. Fitted with 354mm handle for extra leverage.

Model No:	LB001	LB002
Working Load:	2500kg	4200kg
Breaking Strength:.....	8636kg	8636kg
Chain Size:	7.9-9.5mm	9.5-12.7mm
Handle Length:	354mm	354mm
Hook:	Double	Double
Weight:	4.8kg	5.9kg

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.


WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.

3. OPERATION


- 3.1.** Arrange chains over load to be secured.
 - 3.1.1.** Ensure that there is thread showing behind each hook of the load binder to allow it to wind in.
 - 3.1.2.** Hook binder through each end of the chain and operate ratchet pawl to pull the chain into tension.
 - 3.1.3.** Tie off any slack chain.





 **Environmental Protection.**
Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycle centre and disposed of in a manner which is compatible with the environment.



Sole UK Distributor, Sealey Group,
Kempson Way, Suffolk Business Park,
Bury St. Edmunds, Suffolk,
IP32 7AR

 01284 757500

 01284 703534

 www.sealey.co.uk

 sales@sealey.co.uk